

ELECTRIC STACKER

SE1225P

SE1229P

SE1235P



SE1225P • SE1229P • SE1235P

TECHNICAL DETAILS				SE1225P	SE1229P	SE1235P
CAPACITY	Q	Nominal load	Kg	1200	1200	1200
CENTER OF GRAVITY	C	Distance	mm	600	600	600
DRIVING SYSTEM		Escort / Standing		Escort	Escort	Escort
DIMENSIONS						
ELEVATION	h3	Elevation	mm	2500	2900	3500
	h2	Normal free elevation	mm	-	-	80
LENGTH	l	Fork length	mm	1150	1150	1150
	nxS1	Fork width x thickness	mm	150X70	150X70	150X70
DIMENSIONS	L	Total length	mm	1825	1825	1825
	L2	Steer unit length	mm	675	675	675
	B	Width	mm	850	850	850
	h1	Minimum dimensions	mm	1780	1980	2250
	h4	Maximum dimensions	mm	2985	3385	3915
TURNING RADIUS	Wa		mm	1460	1460	1460
STOWAGE PASSAGE	Ast		mm	2075	2075	2075
PERFORMANCES						
SPEED		Translation with/without load	km/h	4,0/5,0	4,0/5,0	4,0/5,0
LIFTING		With/without load	m/s	0,07/0,10	0,07/0,10	0,07/0,10
DESCENT		With/without load	m/s	0,4/0,1	0,4/0,1	0,4/0,1
WEIGHT						
EMPTY WEIGHT		With battery	kg	524	539	574
AXLE LOADING		With load (driver/load)	kg	573/1151	587/1152	613/1161
		Without load (driver/load)	kg	386/138	400/139	426/148
FRAME						
WHEELS		Driver side/load	Nr	2+1 M/2	2+1 M/2	2+1 M/2
TYRES		Driver side/load		P+G/P	P+G/P	P+G/P
		Drive wheel Ø	mm	250X76	250X76	250X76
		Stabilizer wheels Ø	mm	150X40	150X40	150X40
		Load side Ø	mm	82X70	82X70	82X70
OPERATING BRAKE				Electric	Electric	Electric
ELECTRICAL EQUIPMENT						
ELECTRIC MOTORS		Traction motor	kW	0,7	0,7	0,7
		Lifting motor	kW	2,2	2,2	2,2
SPEED CONTROL				Electric	Electric	Electric
BATTERY		Traction/Starter	type	T	T	T
		Voltage	V	24	24	24
		Capacity	Ah	100	100	100
		Endurance	h	5	5	5
		Weight	kg	78	78	78
CHARGER			V-A	24-20	24-20	24-20

G=Rubber, P=Polyurethane

